

```

<?xml version="1.0" encoding="UTF-8"?>
<!-- version 版本号，必须。 EchoToken:必须，按南航定义的规则产生 -->
<SeatAvailabilityRQ Version="17.2"
EchoToken="254146983780723666287721047005372212923483704689"
xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2
SeatAvailabilityRQ.xsd"
xmlns="http://www.iata.org/IATA/EDIST/2017.2"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!-- 文档信息 ,必须 -->
  <Document>
    <!-- 国际国内标识： 必须， 0 国际， 1 国内 -->
    <Name>0</Name>
  </Document>
  <!-- 请求单位信息， 必须 -->
  <Party>
    <!-- 发送人信息 ， 必须-->
    <Sender>
      <!-- 南航分配渠道 ID ， 必须 -->
      <CorporateSender>
        <!-- 必须 -->
        <Name></Name>
        <!-- 必须 -->
        <ID></ID>
        <!-- 可选 -->
        <CorporateCode></CorporateCode>
      </CorporateSender>
    </Sender>
  </Party>
  <Query>
    <!-- 机票订单号， 必须 -->
    <Order Owner="CZ" OrderID="C1812250000215"></Order>
    <!-- PNR 必须， AirlineID 固定 CZ -->
    <BookingReference>
      <ID>NZ9HTV</ID>
      <AirlineID>CZ</AirlineID>
    </BookingReference>
  </Query>
  <!-- 数据组， 必须 -->
  <DataLists>
    <!-- 联系方式， 必须 -->
    <ContactList>
      <ContactInformation>
        <ContactProvided>
          <Phone>

```

```
        <!-- 联系电话, 必须 -->
        <PhoneNumber>15858585588</PhoneNumber>
    </Phone>
</ContactProvided>
</ContactInformation>
</ContactList>
</DataLists>
</SeatAvailabilityRQ>
```

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- version 版本号, 必须。 EchoToken 按南航定义的规则产生-->
<SeatAvailabilityRS Version="17.2"
EchoToken="254146983780723666287721047005372212923483704689"
TimeStamp="2018-12-26T15:00:48"
xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2
SeatAvailabilityRS.xsd"
xmlns="http://www.iata.org/IATA/EDIST/2017.2"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <!-- 文档信息 ,必须 -->
    <Document>
        <!-- 订单号, 必须 -->
        <Name>C1812250000215</Name>
    </Document>
    <!-- 成功标识, 必须 -->
    <Success />
    <!-- 座位信息 , 必须 Owner 固定 Z9-->
    <ALaCarteOffer OfferID="OFSeat001" Owner="Z9">
        <!-- 时间限制, 必须 -->
        <TimeLimits>
            <OfferExpiration DateTime="2018-12-26T09:24:05"/>
        </TimeLimits>
        <!-- 座位旅客关联信息, 必须 -->
        <ALaCarteOfferItem OfferItemID="OfferItemSeat01">
            <!-- 旅客航段关联, 必须 -->
            <Eligibility>
                <!-- 旅客, 必须 -->
                <PassengerRefs>psg1</PassengerRefs>
                <!-- 航段, 必须 -->
                <SegmentRefs>seg1</SegmentRefs>
            </Eligibility>
            <!-- 价格信息, 必须 -->
```

```
<UnitPriceDetail>
  <!-- 总计，必须 -->
  <TotalAmount>
    <!-- 金额，必须。Code:币种，必须 -->
    <SimpleCurrencyPrice
Code="CNY">600.0</SimpleCurrencyPrice>
  </TotalAmount>
</UnitPriceDetail>
<!-- 暂无作用 -->
<Service ServiceID="SIDSeat0001">
  <ServiceDefinitionRef>SIDSeat0001</ServiceDefinitionRef>
</Service>
</ALaCarteOfferItem>
</ALaCarteOffer>
<!--座位图信息，必须 -->
<SeatMap>
  <!-- 航段，必须 -->
  <SegmentRef>seg1</SegmentRef>
  <!-- 舱位信息，必须 -->
  <Cabin>
    <!-- 舱位类型，必须 -->
    <CabinType>
      <!-- 舱位代码，必须 -->
      <Code>Y</Code>
    </CabinType>
    <!-- 舱位区域，必须 -->
    <CabinLayout>
      <!-- 第几列，必须-->
      <Columns>A</Columns>
      <Columns>B</Columns>
      <Rows>
        <!-- 起始行，必须-->
        <First>14</First>
        <!-- 结束行，必须-->
        <Last>15</Last>
      </Rows>
    </CabinLayout>
    <!-- 行，必须-->
    <Row>
      <!-- 行号，必须-->
      <Number>14</Number>
      <!-- 座位 -->
      <Seat>
        <!-- 列号，必须-->
```

```
<Column>A</Column>
<!-- 座位状态 ， 必须-->
<SeatStatus>U</SeatStatus>
<!-- 座位属性 ， 必须-->
<SeatCharacteristics>
    <!-- 属性代码 ， 必须-->
    <Code>E</Code>
</SeatCharacteristics>
<!-- 关联座位信息 ， 必须-->
<OfferItemRefs>OfferItmSeat01</OfferItemRefs>
</Seat>
<Seat>
    <!-- 列号 -->
    <Column>B</Column>
    <!-- 座位状态 -->
    <SeatStatus>U</SeatStatus>
    <!-- 座位属性 -->
    <SeatCharacteristics>
        <!-- 属性代码 -->
        <Code>E</Code>
    </SeatCharacteristics>
    <!-- 关联座位信息 -->
    <OfferItemRefs>OfferItmSeat01</OfferItemRefs>
</Seat>
</Row>
<Row>
    <!-- 行号 -->
    <Number>15</Number>
    <!-- 座位 -->
    <Seat>
        <!-- 列号 -->
        <Column>A</Column>
        <!-- 座位状态 -->
        <SeatStatus>U</SeatStatus>
        <!-- 座位属性 -->
        <SeatCharacteristics>
            <!-- 属性代码 -->
            <Code>E</Code>
        </SeatCharacteristics>
        <!-- 关联座位信息 -->
        <OfferItemRefs>OfferItmSeat01</OfferItemRefs>
    </Seat>
    <Seat>
        <!-- 列号 -->
```

```
<Column>B</Column>
<!-- 座位状态 -->
<SeatStatus>U</SeatStatus>
<!-- 座位属性 -->
<SeatCharacteristics>
  <!-- 属性代码 -->
  <Code>E</Code>
</SeatCharacteristics>
<!-- 关联座位信息 -->
<OfferItemRefs>OfferItmSeat01</OfferItemRefs>
</Seat>
</Row>
</Cabin>
</SeatMap>
<!--座位图信息，必须 -->
<SeatMap>
  <!-- 航段，必须 -->
  <SegmentRef>seg2</SegmentRef>
  <!-- 舱位信息，必须 -->
  <Cabin>
    <!-- 舱位类型，必须 -->
    <CabinType>
      <!-- 舱位代码，必须 -->
      <Code>Y</Code>
    </CabinType>
    <!-- 舱位区域，必须 -->
    <CabinLayout>
      <!-- 第几列 -->
      <Columns>A</Columns>
      <Columns>B</Columns>
      <Rows>
        <!-- 起始行 -->
        <First>14</First>
        <!-- 结束行 -->
        <Last>15</Last>
      </Rows>
    </CabinLayout>
    <!-- 行 -->
    <Row>
      <!-- 行号 -->
      <Number>14</Number>
      <!-- 座位 -->
      <Seat>
        <!-- 列号 -->
```

```
<Column>A</Column>
<!-- 座位状态 -->
<SeatStatus>U</SeatStatus>
<!-- 座位属性 -->
<SeatCharacteristics>
  <!-- 属性代码 -->
  <Code>E</Code>
</SeatCharacteristics>
<!-- 关联座位信息 -->
<OfferItemRefs>OfferItmSeat01</OfferItemRefs>
</Seat>
<Seat>
  <!-- 列号 -->
  <Column>B</Column>
  <!-- 座位状态 -->
  <SeatStatus>U</SeatStatus>
  <!-- 座位属性 -->
  <SeatCharacteristics>
    <!-- 属性代码 -->
    <Code>E</Code>
  </SeatCharacteristics>
  <!-- 关联座位信息 -->
  <OfferItemRefs>OfferItmSeat01</OfferItemRefs>
</Seat>
</Row>
<Row>
  <!-- 行号 -->
  <Number>15</Number>
  <!-- 座位 -->
  <Seat>
    <!-- 列号 -->
    <Column>A</Column>
    <!-- 座位状态 -->
    <SeatStatus>U</SeatStatus>
    <!-- 座位属性 -->
    <SeatCharacteristics>
      <!-- 属性代码 -->
      <Code>E</Code>
    </SeatCharacteristics>
    <!-- 关联座位信息 -->
    <OfferItemRefs>OfferItmSeat01</OfferItemRefs>
  </Seat>
  <Seat>
    <!-- 列号 -->
```

```

        <Column>B</Column>
        <!-- 座位状态 -->
        <SeatStatus>U</SeatStatus>
        <!-- 座位属性 -->
        <SeatCharacteristics>
            <!-- 属性代码 -->
            <Code>E</Code>
        </SeatCharacteristics>
        <!-- 关联座位信息 -->
        <OfferItemRefs>OfferItmSeat01</OfferItemRefs>
    </Seat>
</Row>
</Cabin>
</SeatMap>
<!-- 数据组 ， 必须-->
<DataLists>
    <!-- 旅客信息列表 ， 必须-->
    <PassengerList>
        <!-- 旅客信息 ， 必须-->
        <Passenger PassengerID="psg1">
            <!-- 旅客类型 ， 必须-->
            <PTC>ADT</PTC>
            <!-- 姓名 ， 必须-->
            <Individual>
                <!-- 名 -->
                <GivenName>Jane</GivenName>
                <!-- 姓 -->
                <Surname>Smith</Surname>
            </Individual>
        </Passenger>
    </PassengerList>
    <!-- 航段列表 ， 必须-->
    <FlightSegmentList>
        <!-- 航段信息 ， 必须-->
        <FlightSegment SegmentKey="seg1">
            <!-- 起飞信息 ， 必须-->
            <Departure>
                <!-- 起飞机场 ， 必须-->
                <AirportCode>CAN</AirportCode>
                <!-- 起飞日期 ， 必须-->
                <Date>2018-06-01</Date>
            </Departure>
            <!-- 到达信息 ， 必须-->
            <Arrival>

```

```
<!-- 到达机场 ， 必须-->
  <AirportCode>PEK</AirportCode>
  <!-- 到达日期 ， 必须-->
  <Date>2018-06-01</Date>
</Arrival>
<!-- 销售航班信息 ， 必须-->
<MarketingCarrier>
  <!-- 销售承运人 -->
  <AirlineID>CZ</AirlineID>
  <!-- 航班号 -->
  <FlightNumber>324</FlightNumber>
</MarketingCarrier>
</FlightSegment>
<FlightSegment SegmentKey="seg2">
  <Departure>
    <AirportCode>PEK</AirportCode>
    <Date>2018-06-01</Date>
  </Departure>
  <Arrival>
    <AirportCode>CAN</AirportCode>
    <Date>2018-06-01</Date>
  </Arrival>
  <MarketingCarrier>
    <AirlineID>CZ</AirlineID>
    <FlightNumber>324</FlightNumber>
  </MarketingCarrier>
</FlightSegment>
</FlightSegmentList>
<!-- 暂无作用 -->
<ServiceDefinitionList>
  <ServiceDefinition ServiceDefinitionID="Seat01"
    Owner="Z9">
    <Name>Seat Assignment 01</Name>
    <Descriptions>
      <Description>
        <Text>Seat Assignment Service</Text>
      </Description>
    </Descriptions>
  </ServiceDefinition>
</ServiceDefinitionList>
</DataLists>
</SeatAvailabilityRS>
```



```

<?xml version="1.0" encoding="UTF-8"?>
<OrderCreateRQ                                     Version="String"
xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2 ..../OrderCreateRQ.xsd"
xmlns="http://www.iata.org/IATA/EDIST/2017.2"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!-- 文档信息 -->
  <Document/>
  <!-- 请求单位信息 -->
  <Party>
    <!-- 发送人信息 -->
    <Sender>
      <!-- 合作方 -->
      <CorporateSender>
        <!-- 名称 -->
        <Name>XYZ Corporation</Name>
        <!-- ID -->
        <ID>system</ID>
        <!-- 代号 -->
        <CorporateCode>XYZ</CorporateCode>
      </CorporateSender>
    </Sender>
  </Party>
  <!-- 请求信息 -->
  <Query>
    <!-- 订单信息 -->
    <Order>
      <!-- offer 信息 -->
      <Offer      Owner="CZ"      ResponseID="321s65df4a5465sa46df"
OfferID="OFSeat001">
        <!-- 选座信息 -->
        <OfferItem OfferItemID="OfferItmSeat01">
          <!-- 关联旅客 -->
          <PassengerRefs>psg1</PassengerRefs>
          <!-- 座位信息 -->
          <SeatSelection>
            <!-- 行 -->
            <Row>14</Row>
            <!-- 列 -->
            <Column>A</Column>
          </SeatSelection>
        </OfferItem>
        <OfferItem OfferItemID="OfferItmSeat02">
          <PassengerRefs>psg1</PassengerRefs>
          <ALaCarteSelection>

```

```
        <Quantity>1</Quantity>
        <SegmentID>seg2</SegmentID>
    </ALaCarteSelection>
    <SeatSelection>
        <Row>14</Row>
        <Column>B</Column>
    </SeatSelection>
</OfferItem>
<OfferItem OfferItemID="OfferItmSeat01">
    <PassengerRefs>psg2</PassengerRefs>
    <ALaCarteSelection>
        <Quantity>1</Quantity>
        <SegmentID>seg1</SegmentID>
    </ALaCarteSelection>
    <SeatSelection>
        <Row>15</Row>
        <Column>C</Column>
    </SeatSelection>
</OfferItem>
<OfferItem OfferItemID="OfferItmSeat02">
    <PassengerRefs>psg2</PassengerRefs>
    <ALaCarteSelection>
        <Quantity>1</Quantity>
        <SegmentID>seg2</SegmentID>
    </ALaCarteSelection>
    <SeatSelection>
        <Row>15</Row>
        <Column>D</Column>
    </SeatSelection>
</OfferItem>
</Offer>
</Order>
<!-- 数据组 -->
<DataLists>
    <!-- 旅客信息集合 -->
    <PassengerList>
        <!-- 旅客信息 -->
        <Passenger PassengerID="psg1">
            <!-- 旅客类型 -->
            <PTC>ADT</PTC>
            <!-- 年龄 -->
            <Age>30</Age>
            <!-- 身份信息 -->
            <IdentityDocument>
```

```

        <!-- 证件号 -->
    <IdentityDocumentNumber>440582198812455245</IdentityDocumentNumber
>
        <!-- 证件类型 -->
        <IdentityDocumentType>1</IdentityDocumentType>
        <!-- 出生日期 -->
        <Birthdate>1988-06-01</Birthdate>
        <!-- 名 -->
        <GivenName>a</GivenName>
        <!-- 中间名 -->
        <MiddleName>b</MiddleName>
        <!-- 姓 -->
        <Surname>c</Surname>
    </IdentityDocument>
</Passenger>
<Passenger PassengerID="psg2">
    <PTC>ADT</PTC>
    <Age>30</Age>
    <IdentityDocument>
        <IdentityDocumentNumber>440582198812455245</IdentityDocumentNumber
>
            <IdentityDocumentType>1</IdentityDocumentType>
            <Birthdate>1988-06-01</Birthdate>
            <GivenName>c</GivenName>
            <MiddleName>d</MiddleName>
            <Surname>f</Surname>
        </IdentityDocument>
    </Passenger>
</PassengerList>
</DataLists>
</Query>
</OrderCreateRQ>

<?xml version="1.0" encoding="UTF-8"?>
<OrderViewRS Version="String"
    xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2 ../OrderViewRS.xsd"
    xmlns="http://www.iata.org/IATA/EDIST/2017.2"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <!-- 文档信息 -->
    <Document />

```

```
<!-- 请求单位信息 -->
<Party>
  <!-- 发送人信息 -->
  <Sender>
    <!-- 合作方 -->
    <CorporateSender>
      <!-- 名称 -->
      <Name>XYZ Corporation</Name>
      <!-- ID -->
      <ID>system</ID>
      <!-- 代号 -->
      <CorporateCode>XYZ</CorporateCode>
    </CorporateSender>
  </Sender>
</Party>
<!-- 成功标志 -->
<Success/>
<!-- 返回信息 -->
<Response>
  <!-- GO 单信息 -->
  <Order Owner="CZ" OrderID="GO180612000001">
    <!-- 订单组信息 -->
    <OrderItems>
      <!-- 订单信息 -->
      <OrderItem OrderItemID="SO180612000001">
        <!-- 订单状态 -->
        <ItemStatus>E</ItemStatus>
        <!-- 价格信息 -->
        <PriceDetail>
          <!-- 总价 -->
          <TotalAmount Code="CNY">
            <SimpleCurrencyPrice>120.00</SimpleCurrencyPrice>
          </TotalAmount>
          <!-- 支付价 -->
          <BaseAmount Code="CNY">100.00</BaseAmount>
          <!-- 优惠信息 -->
          <Discount>
            <DiscountAmount
Code="CNY">20.00</DiscountAmount>
          </Discount>
        </PriceDetail>
      </OrderItem>
      <OrderItem OrderItemID="SO180612000002">
        <ItemStatus>E</ItemStatus>
```

```

        <PriceDetail>
            <TotalAmount Code="CNY">
                <SimpleCurrencyPrice>120.00</SimpleCurrencyPrice>
            </TotalAmount>
            <BaseAmount Code="CNY">100.00</BaseAmount>
            <Discount>
                <DiscountAmount
Code="CNY">20.00</DiscountAmount>
            </Discount>
        </PriceDetail>
    </OrderItem>
</OrderItems>
</Order>
</Response>
</OrderViewRS>

```

```

<?xml version="1.0" encoding="UTF-8"?>
<!-- version 版本号, 必须。 EchoToken:必须, 按南航定义的规则产生 -->
<OrderCancelRQ Version="17.2"
EchoToken="254146983780723666287721047005372212923483704689"
xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2
OrderCancelRQ.xsd"
xmlns="http://www.iata.org/IATA/EDIST/2017.2"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <!-- 文档信息 ,必须, 写死 -->
    <Document/>
    <!-- 请求单位信息, 必须 -->
    <Party>
        <!-- 发送人信息, 必须 -->
        <Sender>
            <!-- 合作方, 必须 -->
            <CorporateSender>
                <!-- 名称, 必须 -->
                <Name></Name>
                <!-- ID, 必须-->
                <ID></ID>
                <!-- 代号,可选 -->
                <CorporateCode></CorporateCode>
            </CorporateSender>
        </Sender>
    </Party>
    <!-- 必传, 支付总额 -->
    <ExpectedRefundAmount>

```

```
        <Total>1000</Total>
    </ExpectedRefundAmount>
    <!-- 必传, 选座 GO 单 -->
    <Query>
        <Order Owner="CZ" OrderID="GO1805010000012" />
    </Query>
</OrderCancelRQ>
```

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- version 版本号, 必须。 EchoToken 按南航定义的规则产生-->
<OrderCancelRS Version="17.2"
EchoToken="254146983780723666287721047005372212923483704689"
TimeStamp="2018-12-26T15:00:48"
xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2
OrderCancelRS.xsd"
xmlns="http://www.iata.org/IATA/EDIST/2017.2"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <!-- 文档信息 ,必须, 写死 -->
    <Document/>
    <!-- 成功标识, 必须 -->
    <Success/>
    <!-- 响应信息, 必须 -->
    <Response>
        <!-- 取消的订单号, 必须 -->
        <OrderReference>GO1812250000012</OrderReference>
    </Response>
</OrderCancelRS>
```

```
<?xml version="1.0" encoding="UTF-8"?>
<AirDocIssueRQ Version="17.2" xmlns="http://www.iata.org/IATA/EDIST/2017.2"
PrimaryLangID="EN"
EchoToken="-578949598181878006621748562495072371692474262756"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2 AirDocIssueRQ.xsd">
```

```
    <!-- 文档信息 -->
    <Document />
    <!-- 请求单位信息 -->
    <Party>
        <!-- 发送人信息 -->
        <Sender>
            <!-- 合作方 -->
```

```

        <CorporateSender>
            <Name></Name>
            <ID></ID>
        </CorporateSender>
    </Sender>
</Party>
<!-- -->
<Query>
    <!-- 必须，写死 1 -->
    <TicketDocQuantity>1</TicketDocQuantity>
    <TicketDocInfo>
        <!-- 必须，指向 PassengerList 中的旅客 PassengerID -->
        <PassengerReference>passenger</PassengerReference>
        <Payments>
            <Payment>
                <Type>CA</Type>
                <Method>
                    <Other>
                        <!-- 必须，易宝支付 易航宝-->
                        <Remarks>
                            <Remark>YEEPAY</Remark>
                        </Remarks>
                    </Other>
                </Method>
                <!-- 必须，支付金额 -->
                <Amount>3000</Amount>
                <!-- 必须，订单号 -->
                <Order Owner="CZ" OrderID="SO1808070000165">
                    <!-- 必须，写死 O1 -->
                    <OrderItemID>O1</OrderItemID>
                </Order>
            </Payment>
        </Payments>
    </TicketDocInfo>
    <DataLists>
        <PassengerList>
            <Passenger PassengerID="passenger">
                <PTC>ADT</PTC>
                <Individual>
                    <!-- 名字 -->
                    <GivenName>名</GivenName>
                    <!-- 姓氏 -->
                    <Surname>张</Surname>
                </Individual>
            </Passenger>
        </PassengerList>
    </DataLists>
</Query>

```

```

        <LoyaltyProgramAccount>
            <AccountNumber>480007017385</AccountNumber>
        </LoyaltyProgramAccount>
        <ContactInfoRef>contact_info</ContactInfoRef>
    </Passenger>
</PassengerList>
<ContactList>
    <!-- 必须, 联系方式 -->
    <ContactInformation ContactID="contact_info">
        <ContactProvided>
            <Phone>
                <PhoneNumber>13612345678</PhoneNumber>
            </Phone>
        </ContactProvided>
    </ContactInformation>
</ContactList>
</DataLists>
</Query>
</AirDocIssueRQ>

```

```

<?xml version="1.0" encoding="UTF-8"?>
<OrderViewRS Version="" xmlns="http://www.iata.org/IATA/EDIST/2017.2"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2
OrderViewRS.xsd">
    <Document/>
    <Success/>
    <Response>
        <Order OrderID="SO1808200000126" Owner="CZ">
            <OrderItems>
                <OrderItem OrderItemID="o1">
                    <!-- 订单状态 -->
                    <ItemStatus>E</ItemStatus>
                    <PriceDetail>
                        <!-- 金额 -->
                        <BaseAmount>1960.00</BaseAmount>
                    </PriceDetail>
                    <Service ServiceID="service">
                        <PassengerRef>passenger</PassengerRef>
                        <!-- 支付流水 -->
                    </Service>
                </OrderItem>
            </OrderItems>
        </Order>
    </Response>
    <ServiceDefinitionRef>YEE020160921892664</ServiceDefinitionRef>
</OrderViewRS>

```



```

        </OrderItem>
    </OrderItems>
</Order>
<DataLists>
    <PassengerList>
        <Passenger PassengerID="passenger">
            <PTC>ADT</PTC>
            <Individual>
                <!-- 名字 -->
                <GivenName>名</GivenName>
                <!-- 姓氏 -->
                <Surname>张</Surname>
            </Individual>
        </Passenger>
    </PassengerList>
    <ServiceDefinitionList>
        <!-- 支付流水作为 ID -->
        <ServiceDefinition ServiceDefinitionID="YEE020160921892664">
            <!-- 支付网关 -->
            <Name>YEEPAY</Name>
            <Descriptions>
                <Description>
                    <!-- 支付表单 -->
                </Description>
            </Descriptions>
            <Text>X2lucHV0X2NoYXJzZXQ91c2VyJnBhcnRuZXI</Text>
        </ServiceDefinition>
    </ServiceDefinitionList>
</DataLists>
</Response>
</OrderViewRS>

<?xml version="1.0" encoding="UTF-8"?>
<!-- Version 版本信息写死 17.2, EchoToken 必须, 按南航定义的规则产生 (The
version information is
    written to 17.2, EchoToken must be generated according to the rules defined
    by China Southern Airlines) -->
<OrderRetrieveRQ Version="17.2"
    xmlns="http://www.iata.org/IATA/EDIST/2017.2"
    EchoToken="710696544195218791570932214654160794061432985412"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2
    OrderRetrieveRQ.xsd">

```

```

<!-- 必须，但暂时未使用 (Required,but not yet use) -->
<Document />
<!-- 请求单位信息 -->
<Party>
  <!-- 发送人信息 -->
  <Sender>
    <!-- 南航分配渠道 ID ， 必须 -->
    <CorporateSender>
      <!-- 必须 -->
      <Name></Name>
      <!-- 必须 -->
      <ID>CTR001</ID>
      <!-- 可选 -->
      <CorporateCode></CorporateCode>
    </CorporateSender>
  </Sender>
</Party>
<Query>
  <Filters>
    <!-- 必须，提取的订单号 (Required,the OrderID wanted) -->
    <OrderID Owner="CZ">GO180101000001</OrderID>
    <!-- 必须，订单中任意一个旅客姓名 -->
    <Passengers>
      <Individual>
        <GivenName>san</GivenName>
        <Surname>zhang</Surname>
      </Individual>
    </Passengers>
  </Filters>
</Query>
</OrderRetrieveRQ>

<?xml version="1.0" encoding="UTF-8"?>
<OrderViewRS Version="String"
  xsi:schemaLocation="http://www.iata.org/IATA/EDIST/2017.2 ../OrderViewRS.xsd"
  xmlns="http://www.iata.org/IATA/EDIST/2017.2"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!-- 文档信息 -->
  <Document />
  <!-- 请求单位信息 -->
  <Party>
    <!-- 发送人信息 -->

```

```
<Sender>
  <!-- 合作方 -->
  <CorporateSender>
    <!-- 名称 -->
    <Name>XYZ Corporation</Name>
    <!-- ID -->
    <ID>system</ID>
    <!-- 代号 -->
    <CorporateCode>XYZ</CorporateCode>
  </CorporateSender>
</Sender>
</Party>
<!-- 成功标志 -->
<Success/>
<!-- 返回信息 -->
<Response>
  <!-- GO 单信息 -->
  <Order Owner="CZ" OrderID="GO1806120000001">
    <!-- 订单组信息 -->
    <OrderItems>
      <!-- 订单信息 -->
      <OrderItem OrderItemID="SO1806120000001">
        <!-- 订单状态 -->
        <ItemStatus>E</ItemStatus>
        <!-- 价格信息 -->
        <PriceDetail>
          <!-- 总价 -->
          <TotalAmount Code="CNY">
            <SimpleCurrencyPrice>120.00</SimpleCurrencyPrice>
          </TotalAmount>
          <!-- 支付价 -->
          <BaseAmount Code="CNY">100.00</BaseAmount>
          <!-- 优惠信息 -->
          <Discount>
            <DiscountAmount
Code="CNY">20.00</DiscountAmount>
          </Discount>
        </PriceDetail>
      </OrderItem>
      <OrderItem OrderItemID="SO1806120000002">
        <ItemStatus>E</ItemStatus>
        <PriceDetail>
          <TotalAmount Code="CNY">
            <SimpleCurrencyPrice>120.00</SimpleCurrencyPrice>
```

```
        </TotalAmount>
        <BaseAmount Code="CNY">100.00</BaseAmount>
        <Discount>
            <DiscountAmount
Code="CNY">20.00</DiscountAmount>
            </Discount>
        </PriceDetail>
    </OrderItem>
</OrderItems>
</Order>
</Response>
</OrderViewRS>
```